

**POWER EVERYDAY!**

**Cummins Generator**

**GDD-C1375**

**KTA50-G8**

**Prime Power: 1100KW/1375KVA**

**Standby Power: 1210KW/1513KVA**



**Increased availability for new operations**

Reliable, robust and versatile generator.  
Ready to deliver power for a next job.

**Increased uptime during operations**

Once installed on the end-user-site, the generator will be ready to run: "peace of mind" operation.

**Reduced transport and installation costs**


The compact and robust design with integrated transport features enables faster and safer transport and installation.

**Reduced service & maintenance costs**

Longer service intervals.  
Quicker and more efficient service jobs.

**Premium resale value**

Designed and built to last.

 <b>SAFETY</b>
<ul style="list-style-type: none"><li>● Operate safely in accordance with proper operation manual.</li><li>● To prevent trouble and accidents, perform daily and preventive maintenance checks without fail.</li></ul>

**Cummins Series**

25KVA--1400KVA



**Xiamen Goldengorry Electric Machinery  
Imp and Exp Co., Ltd.**

**Fujian Rawsun Power Co., Ltd.**

Factory: Changtai Industry Zone, Zhangzhou, Fujian, China

Tel: +86-0596-8225007 Fax: +86-0596-8225006

E-mail: sales@goldengorry.com

Web: www.goldengorry.com or www.rawsunpower.com

# Technical Data

Type		GDD-C1350
		<b>50Hz</b>
Rated speed	r/min	1500
Rated power factor(lagging)		0.8
Rated prime power	Kw/KVA	1100/1375
Rated standby power	Kw/KVA	1210/1513
Sound power level	dB(A)	open type

## Basic unit

### Fuel autonomy

full load	L/h	289
75% load	L/h	222
50% load	L/h	155
Capacity fuel tank	L	3000
		(External Fuel Tank)

## Engine-Cummins

Model		KTA50-G8
Rated net power(with fan)	Kw	1200
Displacement	Liquid	50.3
No. cylinders		16
Bore*Stroke	mm	159*159
Coolant	Liquid	315
Aspiration		Turbo, Air/Water cooling

## Alternator-GAS


Model		GAS-734ES
Degree of protection/Insulation class		IP23/H

## Control Panel-Smartgen

Model		HGM 6120
-------	--	----------

## Unit dimensions(Basic unit)

L*W*H(Open style)	m	5560*2050*2310
(Soundproof style)	m	40'ft container
Weight(Open type)	kg	11140
(Soundproof type)	kg	18900




## Standard Control Panel

Smartgen HGM 6120



## Options



## Standard Features

Standard Features	GGC
Engine(DCEC Cummins)	●
Radiator 50°C max, fans are driven by belt	●
24V charge alternator	●
Alternator: single bearing alternator IP23, insulation class H/H	●
Goldengorry standard auto control system	●
One set of air filter, fuel filter, oil filter	●
Main line circuit breaker/MCCB	●
Base fuel tank	●
Two 12V batteries, rac and cable	●
Exhaust system(Ripple flex exhaust pipe, exhaust siphon, flange, muffler)	●
User manual	●

## Options

Battery charge	○
Engine heater	○
Alternator heater	○
Water separator	○
Remote control panel	○
Automatic transfer switch/ATS	○
Switch box	○
Standard:	●
Options:	○

## Warranty\*

### Cummins Engine

12 months from date of purchase and 1000 hours.

### Generator

12 months from date of purchase or 1000 hours(whichever occurs first).

More information, pls refer to our web-site: [www.goldengorry.com](http://www.goldengorry.com) or [www.rawsunpower.com](http://www.rawsunpower.com)

Manufacturer reserves the right to make changes in model, technical specification, color, equipment and accessories without notice.