

POWER EVERYDAY!

Cummins Generator

GDD-C275S

NTA855-G1A

Prime Power: 220KW/275KVA

Standby Power: 242KW/303KVA



Increased availability for new operations

Reliable, robust and versatile generator.
Ready to deliver power for a next job.

Increased uptime during operations

Once installed on the end-user-site, the generator will be ready to run: "peace of mind" operation.

Reduced transport and installation costs

The compact and robust design with integrated transport features enables faster and safer transport and installation.

Reduced service & maintenance costs

Longer service intervals.
Quicker and more efficient service jobs.

Premium resale value

Designed and built to last.

SAFETY

- Operate safely in accordance with proper operation manual.
- To prevent trouble and accidents, perform daily and preventive maintenance checks without fail.

Cummins Series

25KVA--1400KVA



GOLDENGORRY

RAWSUNPOWER

Xiamen Goldengorry Electric Machinery

Imp and Exp Co., Ltd.

Fujian Rawsun Power Co., Ltd.

Factory: Changtai Industry Zone, Zhangzhou, Fujian, China

Tel: +86-0596-8225007 Fax: +86-0596-8225006

E-mail: sales@goldengorry.com

Web: www.golddedgorry.com

Technical Data

Type		GDD-C275S
		50hZ
Rated speed	r/min	1500
Rated power factor(lagging)		0.8
Rated prime power	Kw/KVA	220/275
Rated standby power	Kw/KVA	242/303
Sound power level	dB(A)	76

Basic unit

Fuel autonomy

full load	L/h	61.3
75% load	L/h	46.1
50% load	L/h	31.4
Capacity fuel tank	L	550

Engine-Cummins

Model		NTA855-G1A
Rated net power(with fan)	Kw	250
Displacement	Liquid	14
No. cylinders		6
Bore*Stroke	mm	140*152
Coolant	Liquid	45
Aspiration		Turbo, Water/Air cooling

Alternator-Stamford


Model		HCI 444D
Degree of protection/Insulation class		IP23/H

Control Panel-Smartgen

Model		HGM 1780
-------	--	----------

Unit dimensions(Basic unit)

L*W*H(Open style)	m	3100*1100*1850
(Soundproof style)	m	3900*1400*1950
Weight(Open type)	kg	2800
(Soundproof type)	kg	3500



Standard Control Panel

Smartgen HGM1780



Options



Standard Features

Standard Features	GGC
Engine(DCEC Cummins)	●
Radiator 50°C max, fans are driven by belt	●
24V charge alternator	●
Alternator: single bearing alternator IP23, insulation class H/H	●
Goldengorry standard auto control system	●
One set of air filter, fuel filter, oil filter	●
Main line circuit breaker/MCCB	●
Base fuel tank	●
Two 12V batteries, rac and cable	●
Exhaust system(Ripple flex exhaust pipe, exhaust siphon, flange, muffler)	●
User manual	●

Options

Battery charge	○
Engine heater	○
Alternator heater	○
Water separator	○
Remote control panel	○
Automatic transfer switch/ATS	○
Switch box	○
Standard:	●
Options:	○

Warranty*

Cummins Engine

12 months from date of purchase and 1000 hours.

Generator

12 months from date of purchase or 1000 hours(whichever occurs first).

More information, pls refer to our web-site: www.goldengorry.com

Manufacturer reserves the right to make changes in model, technical specification, color, equipment and accessories without notice.