

POWER EVERYDAY!
Doosan Generator
GDD-D200/D200S

P086TI

Prime Power: 160KW/200KVA

Standby Power: 176KW/220KVA



Increased availability for new operations

Reliable, robust and versatile generator.
Ready to deliver power for a next job.

Increased uptime during operations

Once installed on the end-user-site, the generator will be ready to run: "peace of mind" operation.

Reduced transport and installation costs

The compact and robust design with integrated transport features enables faster and safer transport and installation.

Reduced service & maintenance costs

Longer service intervals.
Quicker and more efficient service jobs.

Premium resale value

Designed and built to last.

SAFETY

- Operate safely in accordance with proper operation manual.
- To prevent trouble and accidents, perform daily and preventive maintenance checks without fail.

Doosan Series

55KVA--725KVA



Xiamen Goldengorry Electric Machinery

Imp and Exp Co., Ltd.

Fujian Rawsun Power Co., Ltd.

Factory: Changtai Industry Zone, Zhangzhou, Fujian, China

Tel: +86-0596-8225007 Fax: +86-0596-8225006

E-mail: sales@goldengorry.com

Technical Data

Type	GDD-D200/D200S	
		50hZ
Rated speed	r/min	1500
Rated power factor(lagging)		0.8
Rated prime power	Kw/KVA	160/200
Rated standby power	Kw/KVA	176/220
Sound power level	dB(A)	76

Basic unit

Fuel autonomy

full load	L/h	43.1
75% load	L/h	31.7
50% load	L/h	21.1
Capacity fuel tank	L	400

Engine-Doosan

Model		P086TI
Rated net power(with fan)	Kw	177
Displacement	Liquid	8.1
No. cylinders		6
Bore*Stroke	mm	111*139
Coolant	Liquid	164
Aspiration		Turbo charged

Alternator-GAS


Model		GAS-274H
Degree of protection/Insulation class		IP23/H

Control Panel-Smartgen

Model		HGM 6120
-------	--	----------

Unit dimensions(Basic unit)

L*W*H(Open style)	m	2400*980*1500
(Soundproof style)	m	2950*1100*1550
Weight(Open type)	kg	1500
(Soundproof type)	kg	2000




Standard Control Panel

Smartgen HGM 6120



Options



Standard Features

- Engine(Doosan) ●
- Radiator 50°C max, fans are driven by belt ●
- 24V charge alternator ●
- Alternator: single bearing alternator IP23, insulation class H/H ●
- Goldengorry standard auto control system ●
- One set of air filter, fuel filter, oil filter ●
- Main line circuit breaker/MCCB ●
- Base fuel tank ●
- Two 12V batteries, rac and cable ●
- Exhaust system(Ripple flex exhaust pipe, exhaust siphon, flange, muffler) ●
- User manual ●

GGC

Options

- Battery charge ○
- Engine heater ○
- Alternator heater ○
- Water separator ○
- Remote control panel ○
- Automatic transfer switch/ATS ○
- Switch box ○
- Standard: ● Options: ○

Warranty*

Doosan Engine

12 months from date of purchase and 1000 hours.

Generator

12 months from date of purchase or 1000 hours(whichever occurs first).

Manufacturer reserves the right to make changes in model, technical specification, color, equipment and accessories without notice.

