

# POWER EVERYDAY! Doosan Generator GDD-D363/D363S

## P158LE-1

Prime Power: 290KW/363KVA

Standby Power: 319KW/399KVA



### Increased availability for new operations

Reliable, robust and versatile generator.  
Ready to deliver power for a next job.

### Increased uptime during operations

Once installed on the end-user-site, the generator will be ready to run: "peace of mind" operation.

### Reduced transport and installation costs

The compact and robust design with integrated transport features enables faster and safer transport and installation.

### Reduced service & maintenance costs

Longer service intervals.  
Quicker and more efficient service jobs.

### Premium resale value

Designed and built to last.

### SAFETY

- Operate safely in accordance with proper operation manual.
- To prevent trouble and accidents, perform daily and preventive maintenance checks without fail.

## Doosan Series

69KVA--700KVA



RAWSUNPOWER

**Xiamen Goldengorry Electric Machinery  
Imp and Exp Co., Ltd.  
Fujian Rawsun Power Co., Ltd.**

Factory: Changtai Industry Zone, Zhangzhou, Fujian, China

Tel: +86-0596-8225007 Fax: +86-0596-8225006

E-mail: sales@goldengorry.com

Web: www.golddedgorry.com or www.rawsunpower.com

# Technical Data

Type		GDD-D363/D363S
		<b>60hZ</b>
Rated speed	r/min	1800
Rated power factor(lagging)		0.8
Rated prime power	Kw/KVA	290/363
Rated standby power	Kw/KVA	319/399
Sound power level	dB(A)	77

## Basic unit

### Fuel autonomy

full load	L/h	102.5
75% load	L/h	74.7
50% load	L/h	50.6
Capacity fuel tank	L	726

## Engine-Doosan

Model		P158LE-1
Rated net power(with fan)	Kw	366
Displacement	Liquid	14.618
No. cylinders		8
Bore*Stroke	mm	128*142
Coolant	Liquid	430
Aspiration		Turbo charged

## Alternator-GAS


Model		GAS-314D
Degree of protection/Insulation class		IP23/H

## Control Panel-Smartgen

Model		HGM 6120
-------	--	----------

## Unit dimensions(Basic unit)

L*W*H(Open style)	m	3380*1300*1950
(Soundproof style)	m	3920*1400*1950
Weight(Open type)	kg	2400
(Soundproof type)	kg	3000



## Standard Control Panel

Smartgen HGM6120



## Options



## Standard Features

Standard Features	GGC
Engine(DOOSAN)	●
Radiator 50°C max, fans are driven by belt	●
24V charge alternator	●
Alternator: single bearing alternator IP23, insulation class H/H	●
Goldengorry standard auto control system	●
One set of air filter, fuel filter, oil filter	●
Main line circuit breaker/MCCB	●
Base fuel tank	●
Two 12V batteries, rac and cable	●
Exhaust system(Ripple flex exhaust pipe, exhaust siphon, flange, muffler)	●
User manual	●

## Options

Battery charge	○
Engine heater	○
Alternator heater	○
Water separator	○
Remote control panel	○
Automatic transfer switch/ATS	○
Switch box	○
Standard:	●
Options:	○

## Warranty\*

### Doosan Engine

12 months from date of purchase and 1000 hours.

### Generator

12 months from date of purchase or 1000 hours(whichever occurs first).

More information, pls refer to our web-site: [www.goldengorry.com](http://www.goldengorry.com) or [www.rawsunpower.com](http://www.rawsunpower.com)

Manufacturer reserves the right to make changes in model, technical specification, color, equipment and accessories without notice.