

**POWER EVERYDAY!**  
**Doosan Generator**  
**GDD-D700/D700S**

**P222LE-S**

**Prime Power: 560KW/700KVA**

**Standby Power: 616KW/770KVA**



**Increased availability for new operations**

Reliable, robust and versatile generator.  
Ready to deliver power for a next job.

**Increased uptime during operations**

Once installed on the end-user-site, the generator will be ready to run: "peace of mind" operation.

**Reduced transport and installation costs**

The compact and robust design with integrated transport features enables faster and safer transport and installation.

**Reduced service & maintenance costs**

Longer service intervals.  
Quicker and more efficient service jobs.

**Premium resale value**

Designed and built to last.

**SAFETY**

- Operate safely in accordance with proper operation manual.
- To prevent trouble and accidents, perform daily and preventive maintenance checks without fail.

**Doosan Series**

69KVA--700KVA



**RAWSUNPOWER**

**Xiamen Goldengorry Electric Machinery  
Imp and Exp Co., Ltd.**

**Fujian Rawsun Power Co., Ltd.**

Factory: Changtai Industry Zone, Zhangzhou, Fujian, China

Tel: +86-0596-8225007 Fax: +86-0596-8225006

E-mail: sales@goldengorry.com

Web: www.goldengorry.com or www.rawsunpower.com

# Technical Data

Type	GDD-D700/D700S	
		<b>60hZ</b>
Rated speed	r/min	1800
Rated power factor(lagging)		0.8
Rated prime power	Kw/KVA	560/700
Rated standby power	Kw/KVA	616/770
Sound power level	dB(A)	81

## Basic unit

### Fuel autonomy

full load	L/h	151.6
75% load	L/h	112.3
50% load	L/h	76
Capacity fuel tank	L	1400

## Engine-Doosan

Model		P222LE-S
Rated net power(with fan)	Kw	625
Displacement	Liquid	21.927
No. cylinders		12
Bore*Stroke	mm	128*142
Coolant	Liquid	531
Aspiration		Turbo charged

## Alternator-GAS


Model		GAS-354E
Degree of protection/Insulation class		IP23/H

## Control Panel-Smartgen

Model		HGM 1780
-------	--	----------

## Unit dimensions(Basic unit)

L*W*H(Open style)	m	4450*1750*2350
(Soundproof style)	m	4520*1620*2230
Weight(Open type)	kg	4800
(Soundproof type)	kg	5500




## Standard Control Panel

Smartgen HGM 6120



## Options



## Standard Features

- Engine(DOOSAN) ●
- Radiator 50°C max, fans are driven by belt ●
- 24V charge alternator ●
- Alternator: single bearing alternator IP23, insulation class H/H ●
- Goldengorry standard auto control system ●
- One set of air filter, fuel filter, oil filter ●
- Main line circuit breaker/MCCB ●
- Base fuel tank ●
- Two 12V batteries, rac and cable ●
- Exhaust system(Ripple flex exhaust pipe, exhaust siphon, flange, muffler) ●
- User manual ●

GGC

## Options

- Battery charge ○
- Engine heater ○
- Alternator heater ○
- Water separator ○
- Remote control panel ○
- Automatic transfer switch/ATS ○
- Switch box ○
- Standard: ● Options: ○

## Warranty\*

### Doosan Engine

12 months from date of purchase and 1000 hours.

### Generator

12 months from date of purchase or 1000 hours(whichever occurs first).

More information, pls refer to our web-site: [www.goldengorry.com](http://www.goldengorry.com) or [www.rawsunpower.com](http://www.rawsunpower.com)

Manufacturer reserves the right to make changes in model, technical specification, color, equipment and accessories without notice.