



RAWSUNPOWER

GOLDENGORRY

**SUPER SOUNDPROOF
DIESEL GENERATORS**

MODEL:GDD-Y10S



Genset Features

Increased availability for new operations

Reliable, robust and versatile generator.
Ready to deliver power for a next job.

Increased uptime during operations

Once installed on the end-user-site, the generator will be ready to run: "peace of mind" operation.

Reduced transport and installation costs

The compact and robust design with integrated transport features enables faster and safer transport and installation.

Reduced service & maintenance costs

Longer service intervals.
Quicker and more efficient service jobs.

Power Everyday!
Super Soundproof
58dB(A)@7m

Manufactured by:
**Xiamen Goldengorry Electric Machinery
Imp and Exp Co., Ltd**
Fujian Rawsun Power Co., Ltd.

Add: Changtai Industry Zone, Zhangzhou, Fujian, China
Tel: +86-0596-8225007 Fax: +86-0596-8225006
E-mail: sales@goldengorry.com
Web: www.goldengorry.com or www.rawsunpower.com

SPECIFICATIONS

| MODEL | GDD-Y10S | |
|-------|----------|--|
|-------|----------|--|

| | | |
|-------------------|------------|--|
| ALTERNATOR | | STAMFORD PI 044E |
| Frequency | Hz | 50 |
| Out Rating(KVA) | Continuous | 10 |
| | Standby | 11 |
| No. of Phases | | 1-Phase(2 Wires)or 3-Phase(4 Wires) |
| Rated Voltage | V | 200~400/380~440 |
| Power Factor | | 0.8(Lagging) |
| Excitation | | Brushless(With AVR) |
| Insulation | | Class H/ IP 23 |

ENGINE **YANMAR 3TNV82A-GGE**

| | | |
|---------------------------------|--------|--|
| Type | | Direct injected, Natural aspirated |
| Output Rating | Kw/rpm | 9.9/1500 |
| No. of Cylinders-Bore*Stroke mm | | 3-82*84 |
| Piston Displacement | L | 1.331 |
| Fuel | | ASTM No.2 Diesel Fuel or Equivalent |
| Fuel Consumption | g/kW.h | 245 |
| Battery Capacity | V-Ah | 12V-1*45A |
| Fuel Tank Capacity | L | 20 |

CONTROL SYSTEM **SMARTGEN HGM 1780**

UNIT

| | | |
|------------|----|---------------|
| Dimensions | mm | 1780*780*1150 |
| Dry Weight | kg | 750 |

(Specifications are subject to change without prior notice.)

