



**RAWSUNPOWER**

GOLDENGORRY

**SUPER SOUNDPROOF  
DIESEL GENERATORS**

**MODEL:GDD-Y13S**



### Genset Features

#### Increased availability for new operations

Reliable, robust and versatile generator.  
Ready to deliver power for a next job.

#### Increased uptime during operations

Once installed on the end-user-site, the generator will be ready to run: "peace of mind" operation.

#### Reduced transport and installation costs

The compact and robust design with integrated transport features enables faster and safer transport and installation.

#### Reduced service & maintenance costs

Longer service intervals.  
Quicker and more efficient service jobs.

**Power Everyday!**  
**Super Soundproof**  
**58dB(A)@7m**

**Manufactured by:**  
**Xiamen Goldengorry Electric Machinery  
Imp and Exp Co., Ltd**  
**Fujian Rawsun Power Co., Ltd.**

Add: Changtai Industry Zone, Zhangzhou, Fujian, China

Tel: +86-0596-8225007 Fax: +86-0596-8225006

E-mail: sales@goldengorry.com

Web: www.goldengorry.com or www.rawsunpower.com

### SPECIFICATIONS

MODEL	GDD-Y13S	
-------	----------	--

ALTERNATOR		STAMFORD PI 044F
Frequency	Hz	60
Out Rating(KVA)	Continuous	14.7
	Standby	16.2
No. of Phases		1-Phase(2 Wires)or 3-Phase(4 Wires)
Rated Voltage	V	200~400/380~440
Power Factor		0.8(Lagging)
Excitation		Brushless(With AVR)
Insulation		Class H/ IP 23

#### ENGINE YANMAR 3TNV82A-GGE

Type		Direct injected, Natural aspirated
Output Rating	Kw/rpm	12/1800
No.of Cylinders-Bore*Stroke mm		3-82*84
Piston Displacement	L	1.331
Fuel		ASTM No.2 Diesel Fuel or Equivalent
Fuel Consumption	g/kW.h	245
Battery Capacity	V-Ah	12V-1*45A
Fuel Tank Capacity	L	26

#### CONTROL SYSTEM SMARTGEN HGM 1780

#### UNIT

Dimensions	mm	1780*780*1150
Dry Weight	kg	750

(Specifications are subject to change without prior notice.)

