



**RAWSUNPOWER**

GOLDENGORRY

**SUPER SOUNDPROOF  
DIESEL GENERATORS**

**MODEL:GDD-Y56S**



**56KVA**

### Genset Features

#### Increased availability for new operations

Reliable, robust and versatile generator.  
Ready to deliver power for a next job.

#### Increased uptime during operations

Once installed on the end-user-site, the generator will be ready to run: "peace of mind" operation.

#### Reduced transport and installation costs

The compact and robust design with integrated transport features enables faster and safer transport and installation.

#### Reduced service & maintenance costs

Longer service intervals.  
Quicker and more efficient service jobs.

**Power Everyday!**  
**Super Soundproof**  
**58dB(A)@7m**

**Manufactured by:**  
**Xiamen Goldengorry Electric Machinery  
Imp and Exp Co., Ltd**  
**Fujian Rawsun Power Co., Ltd.**

Add: Changtai Industry Zone, Zhangzhou, Fujian, China  
Tel: +86-0596-8225007 Fax: +86-0596-8225006  
E-mail: sales@goldengorry.com  
Web: www.goldengorry.com or www.rawsunpower.com

### SPECIFICATIONS

MODEL	GDD-Y56S	
-------	----------	--

#### ALTERNATOR **STAMFORD UCI 224E**

Frequency	Hz	50
Out Rating(KVA)	Continuous	60
	Standby	66
No. of Phases	1-Phase(2 Wires) or 3-Phase(4 Wires)	
Rated Voltage	V	200~400/380~440
Power Factor	0.8(Lagging)	
Excitation	Brushless(With AVR)	
Insulation	Class H/ IP 23	

#### ENGINE **YANMAR 4TNV106T-GGE**


Type	Direct injected, Turbocharger	
Output Rating	Kw/rpm	50.9/1500
No. of Cylinders-Bore*Stroke	mm	4-106*125
Piston Displacement	L	4.412
Fuel	ASTM No.2 Diesel Fuel or Equivalent	
Fuel Consumption	g/kW.h	220.4
Battery Capacity	V-Ah	12V-1*80A
Fuel Tank Capacity	L	112

#### CONTROL SYSTEM **SMARTGEN HGM 1780**

#### UNIT

Dimensions	mm	2440*1050*1350
Dry Weight	kg	1150

(Specifications are subject to change without prior notice.)



← L →

← W →

↑ H ↓