

POWER EVERYDAY!
Perkins Generator
GDD-P15/GDD-P15S



403A-15G1

Prime Power: 12.7KW/15.8KVA

Standby Power: 14KW/17.5KVA



Increased availability for new operations

Reliable, robust and versatile generator.
Ready to deliver power for a next job.

Increased uptime during operations

Once installed on the end-user-site, the generator will be ready to run: "peace of mind" operation.

Reduced transport and installation costs


The compact and robust design with integrated transport features enables faster and safer transport and installation.

Reduced service & maintenance costs

Longer service intervals.
Quicker and more efficient service jobs.

Premium resale value

Designed and built to last.

 SAFETY
<ul style="list-style-type: none">● Operate safely in accordance with proper operation manual.● To prevent trouble and accidents, perform daily and preventive maintenance checks without fail.

帕金斯系列

11 KVA--1500 KVA



GOLDENGORRY

RAWSUNPOWER

Xiamen Goldengorry Electric Machinery

Imp and Exp Co., Ltd.

Fujian Rawsun Power Co., Ltd.

Factory: Changtai Industry Zone, Zhangzhou, Fujian, China

Tel: +86-0596-8225007 Fax: +86-0596-8225006

E-mail: sales@goldengorry.com

Web: www.goldengorry.com or www.rawsunpower.com

Specification

Type		GDD-P15/P15S
		60hZ
Rated speed	r/min	1800
Rated power factor(lagging)		0.8
Rated prime power	Kw/KVA	12.7/15.8
Rated standby power	Kw/KVA	14/17.5
Sound power level	dB(A)	63

Basic unit

Fuel autonomy

full load	L/h	3.2
75% load	L/h	2.4
50% load	L/h	1.7
Capacity fuel tank	L	30

Engine-Perkins

Model		403A-15G1
Rated net power(with fan)	Kw	14.7
Displacement	Liquid	1.496
No. cylinders		3
Bore*Stroke	mm	84*90
Coolant	Liquid	6
Aspiration		自然风冷

Alternator-Stamford


Model		PI 044F
Degree of protection/Insulation class		IP23/H

Control Panel-Smartgen

Model		HGM 6120
-------	--	----------

Unit dimensions(Basic unit)

L*W*H(Open style)	m	1250*680*1100
(Soundproof style)	m	1700*750*1000
Weight(Open type)	kg	410
(Soundproof type)	kg	550




Standard Control Panel

Smartgen HGM6120



Options



Standard Features

- Engine(Perkins) ●
- Radiator 50°C max, fans are driven by belt ●
- 24V charge alternator ●
- Alternator: single bearing alternator IP23, insulation class H/H ●
- Goldengorry standard auto control system ●
- One set of air filter, fuel filter, oil filter ●
- Main line circuit breaker/MCCB ●
- Base fuel tank ●
- Two 12V batteries, rac and cable ●
- Exhaust system(Ripple flex exhaust pipe, exhaust siphon, flange, muffler) ●
- User manual ●

GCC

Options

- Battery charge ○
- Engine heater ○
- Alternator heater ○
- Water separator ○
- Remote control panel ○
- Automatic transfer switch/ATS ○
- Switch box ○
- Standard: ● Optional: ○

Warranty*

Perkins Engine

12 months from date of purchase and 1000 hours.

Generator

12 months from date of purchase or 1000 hours(whichever occurs first).