

POWER EVERYDAY! Perkins Generator GDD-P200/GDD-P200S



Perkins Series

11 KVA--1500 KVA



RAWSUNPOWER

1106D-E66TAG4

Prime Power: 160KW/200KVA

Standby Power: 175KW/219KVA



Increased availability for new operations

Reliable, robust and versatile generator.
Ready to deliver power for a next job.

Increased uptime during operations

Once installed on the end-user-site, the generator will be ready to run: "peace of mind" operation.

Reduced transport and installation costs

The compact and robust design with integrated transport features enables faster and safer transport and installation.

Reduced service & maintenance costs

Longer service intervals.

Quicker and more efficient service jobs.

Premium resale value

Designed and built to last.

SAFETY

- Operate safely in accordance with proper operation manual.
- To prevent trouble and accidents, perform daily and preventive maintenance checks without fail.

Xiamen Goldengorry Electric Machinery

Imp and Exp Co., Ltd.

Fujian Rawsun Power Co., Ltd.

Factory: Changtai Industry Zone, Zhangzhou, Fujian, China

Tel: +86-0596-8225007 Fax: +86-0596-8225006

E-mail: sales@goldengorry.com

Web: www.goldengorry.com or www.rawsunpower.com

Specification

Type **GDD-P200/P200S**

		60hZ
Rated speed	r/min	1800
Rated power factor(lagging)		0.8
Rated prime power	Kw/KVA	160/200
Rated standby power	Kw/KVA	175/219
Sound power level	dB(A)	68

Basic unit

Fuel autonomy

full load	L/h	38
75% load	L/h	28
50% load	L/h	20
Capacity fuel tank	L	400

Engine-Perkins

Model		1106D-E66TAG4
Rated net power(with fan)	Kw	186
Displacement	Liquid	6.6
No. cylinders		4
Bore*Stroke	mm	105*127
Coolant	Liquid	21
Aspiration		Turbocharged

Alternator-Stamford


Model		UCI274G
Degree of protection/Insulation class		IP23/H

Control Panel-Smartgen

Model		HGM 6120
-------	--	----------

Unit dimensions(Basic unit)

L*W*H(Open style)	m	2500*900*1400
(Soundproof style)	m	1500
Weight(Open type)	kg	3200*1150*1600
(Soundproof type)	kg	2400



Standard Control Panel

Smartgen HGM6120



Options



Standard Features

- Engine(Perkins) ●
- Radiator 50°C max, fans are driven by belt ●
- 24V charge alternator ●
- Alternator: single bearing alternator IP23, insulation class H/H ●
- Goldengorry standard auto control system ●
- One set of air filter, fuel filter, oil filter ●
- Main line circuit breaker/MCCB ●
- Base fuel tank ●
- Two 12V batteries, rac and cable ●
- Exhaust system(Ripple flex exhaust pipe, exhaust siphon, flange, muffler) ●
- User manual ●

GGC

Options

- Battery charge ○
 - Engine heater ○
 - Alternator heater ○
 - Water separator ○
 - Remote control panel ○
 - Automatic transfer switch/ATS ○
 - Switch box ○
- Standard: ● Optional: ○

Warranty*

Perkins Engine

12 months from date of purchase and 1000 hours.

Generator

12 months from date of purchase or 1000 hours(whichever occurs first).